

## HYBRID MACHINE LEARNING MODEL FOR EFFICIENT BOTNET ATTACK DETECTION IN IOT ENVIRONMENT

<sup>1</sup>DR.C.RAMA KRISHNA, <sup>2</sup>BADAM NAGASREE, <sup>3</sup>MATTA POOJITHA, <sup>4</sup>B SATISH KUMAR, <sup>5</sup>SURYAPALLY DINESHWAR

<sup>1</sup>Assistant Professor, Department of CSE, Malla Reddy Engineering College. Hyderabad, Telangana

<sup>2,3,4,5</sup>Students, Department of CSE, Malla Reddy Engineering College. Hyderabad, Telangana

### ABSTRACT

The rapid growth of Internet of Things (IoT) devices has significantly increased the risk of cyber-attacks, particularly botnet attacks that exploit vulnerable devices to launch distributed malicious activities. Traditional security mechanisms are often insufficient to detect such sophisticated and evolving threats. This project proposes a Hybrid Machine Learning Model for Efficient Botnet Attack Detection in IoT Environment, which combines multiple machine learning techniques to enhance detection accuracy and robustness. The system analyzes network traffic data generated by IoT devices to identify malicious patterns and classify them as normal or botnet activity. The proposed model integrates algorithms such as Random Forest, Support Vector Machine (SVM), and Neural Networks to form a hybrid framework that leverages the strengths of each method. Data preprocessing techniques including feature extraction, normalization, and dimensionality reduction are applied to improve model performance. The hybrid model uses ensemble learning and weighted voting mechanisms to produce accurate predictions. Additionally, real-time monitoring capabilities are incorporated to detect attacks promptly and minimize damage. The performance of the system is evaluated using metrics such as accuracy, precision, recall, F1-score, and detection rate. Experimental results demonstrate that the hybrid approach outperforms individual models in detecting botnet attacks with higher accuracy and lower false positive rates. The system provides a scalable and efficient solution for securing IoT environments against cyber threats. Overall, this project highlights the importance of combining machine learning techniques to build intelligent and adaptive security systems capable of handling complex attack patterns in modern IoT networks.

**Keywords :** IoT Security, Botnet Detection, Machine Learning, Hybrid Model, Cybersecurity, Random Forest, SVM, Neural Networks, Intrusion Detection System, Network Traffic Analysis.

### I.INTRODUCTION

The rapid expansion of the Internet of Things (IoT) has revolutionized modern technology by enabling seamless connectivity between devices such as sensors, smart appliances, and industrial systems. However, this widespread adoption has also introduced significant security challenges, as many IoT devices are resource-constrained and lack robust security mechanisms. One of the most critical threats in IoT environments is botnet attacks, where compromised devices are controlled by attackers to launch distributed attacks such as Distributed Denial of Service (DDoS). These attacks can disrupt services, compromise sensitive data, and cause large-scale damage to networks [1]. Traditional intrusion detection systems often fail to detect such sophisticated attacks due to their dynamic and evolving nature. Therefore, there is a growing need for intelligent and adaptive security solutions that can effectively detect and prevent botnet attacks in IoT networks.

Machine learning has emerged as a powerful tool in cybersecurity for detecting anomalies and identifying malicious patterns in network traffic. Algorithms such as Random Forest, Support Vector Machine (SVM), and Neural Networks can analyze large volumes of data and learn complex relationships between features to distinguish between normal and malicious behavior [2]. However, individual machine learning models may have limitations in terms of accuracy, scalability, or handling diverse attack patterns. To overcome these challenges, hybrid machine learning models have been introduced, combining multiple algorithms to improve detection performance. These hybrid approaches leverage the strengths of different models, such as the robustness of Random Forest, the precision of SVM, and the learning capability of Neural Networks, resulting in enhanced accuracy and reduced false positives.

The proposed project focuses on developing a Hybrid Machine Learning Model for efficient botnet attack detection in IoT environments. The system collects network traffic data and applies preprocessing techniques such as normalization, feature selection, and dimensionality reduction to improve model performance. The hybrid model then analyzes the processed data to classify traffic as normal or malicious. Additionally, the system supports real-time monitoring and alert generation to ensure timely detection of attacks. The performance of the model is evaluated using metrics such as accuracy, precision, recall, and

F1-score to ensure reliability and effectiveness [3]. By integrating multiple machine learning techniques, this project aims to provide a scalable and efficient solution for enhancing IoT security and protecting networks from botnet-based cyber threats.

## II SURVEY OF RESEARCH

The approach proposed by M. Antonakakis and others (2017) [1] focuses on analyzing the Mirai botnet, one of the largest IoT-based cyber-attacks. Their study emphasizes understanding how botnets exploit vulnerable IoT devices to launch distributed attacks. The methodology involves analyzing malware behavior and network traffic patterns. The results demonstrate how easily unsecured IoT devices can be compromised. The authors highlighted the need for stronger security mechanisms in IoT networks. However, the approach does not include machine learning-based detection techniques. Despite this limitation, it provides a strong foundation for understanding botnet behavior.

The study by G. Creech and J. Hu (2014) [2] explores intrusion detection using machine learning techniques. Their approach focuses on anomaly detection using features extracted from network traffic. The methodology involves training models on normal and attack data to identify deviations. The results show improved detection of unknown attacks. The authors emphasized the importance of feature selection in improving accuracy. However, the system may produce higher false positives. Despite this limitation, it contributes to anomaly-based intrusion detection systems.

The work proposed by N. Moustafa and J. Slay (2015) [3] introduces the UNSW-NB15 dataset for network intrusion detection research. Their approach focuses on creating a comprehensive dataset containing modern attack types. The methodology involves generating realistic network traffic and labeling it for training machine learning models. The results demonstrate improved benchmarking for intrusion detection systems. The authors highlighted the importance of high-quality datasets. However, the study does not propose a hybrid model. Despite this limitation, it provides a valuable dataset for training detection systems.

The research by S. Raza, L. Wallgren, and T. Voigt (2013) focuses on lightweight intrusion detection systems for IoT environments [4]. Their approach emphasizes designing security solutions suitable for resource-constrained devices. The methodology involves implementing efficient detection mechanisms with low computational overhead. The results show that lightweight systems can effectively detect attacks in IoT networks. The authors highlighted the importance of energy-efficient security solutions. However, the system lacks advanced machine learning integration. Despite this limitation, it supports the need for efficient IoT security systems.

The study by I. Sharafaldin, A. Lashkari, and A. Ghorbani (2018) [5] focuses on intrusion detection using the CICIDS dataset. Their approach involves analyzing network traffic features to detect cyber-attacks. The methodology includes training machine learning models on labeled data and evaluating their performance. The results demonstrate high detection accuracy for various attack types. The authors emphasized the importance of realistic datasets in cybersecurity research. However, the study does not combine multiple models. Despite this limitation, it provides a strong base for building detection systems.

The work proposed by S. M. P. Dinakarrao and others (2019) [6] focuses on botnet detection in IoT using machine learning techniques. Their approach involves analyzing network traffic patterns to identify botnet behavior. The methodology includes feature extraction and classification using machine learning models. The results show improved detection rates compared to traditional methods. The authors highlighted the importance of intelligent detection systems. However, the system lacks a hybrid model for enhanced performance. Despite this limitation, it contributes to the development of IoT security solutions.

## III. WORKING METHODOLOGY

The proposed system begins with data collection and preprocessing from IoT network environments. Network traffic data is captured from IoT devices such as sensors, smart appliances, and connected systems. This data includes features like packet size, protocol type, source and destination IP addresses, flow duration, and transmission rate. Since raw network data may contain noise, missing values, and redundant features, preprocessing techniques are applied to ensure data quality. These steps include data cleaning, normalization, and feature selection. Normalization is performed to scale features into a common range, improving model performance and convergence. This process can be mathematically expressed as:


$$x' = \frac{x - x_{\min}}{x_{\max} - x_{\min}}$$

Feature selection techniques such as correlation analysis and dimensionality reduction are also applied to remove irrelevant attributes. The processed dataset is then divided into training and testing sets, ensuring that the model learns from historical data and is evaluated on unseen data. Proper preprocessing enhances the accuracy and efficiency of the hybrid model. The second phase focuses on building the hybrid machine learning model by combining multiple algorithms such as Random Forest, Support Vector Machine (SVM), and Neural Networks. Each model contributes unique strengths: Random Forest handles complex patterns, SVM provides high precision in classification, and Neural Networks capture nonlinear relationships. The outputs of these models are combined using an ensemble method such as weighted voting. The prediction of the hybrid model can be represented as:

$$y = \sum_{i=1}^n w_i \cdot h_i(x)$$


where  $h_i(x)$  represents the prediction of each model and  $w_i$  represents its assigned weight. This approach improves overall accuracy and reduces false positives. The models are trained using labeled datasets containing both normal and attack traffic. Optimization techniques such as cross-validation are applied to fine-tune parameters and improve performance. This hybrid approach ensures robust and reliable botnet detection. In the final phase, the trained hybrid model is deployed for real-time botnet attack detection in IoT environments. The system continuously monitors incoming network traffic and classifies it as normal or malicious. If an attack is detected, the system generates alerts and logs the event for further analysis. A feedback mechanism is incorporated to update the model with new data, enabling continuous learning and adaptation to evolving attack patterns. The system performance is evaluated using metrics such as accuracy, precision, recall, F1-score, and detection rate. The hybrid model demonstrates improved detection capability and reduced false alarm rates compared to individual models. Overall, this methodology provides an efficient, scalable, and intelligent solution for securing IoT networks against botnet attacks.

#### IV RESULTS EXPLANATIONS




**Figure 1: Model Accuracy Comparison**

This figure illustrates the performance comparison of individual machine learning models such as Random Forest, Support Vector Machine (SVM), and Neural Network with the proposed Hybrid Model. The graph shows that the Hybrid Model achieves the highest accuracy due to the combination of multiple algorithms. Random Forest performs well in handling complex data, while SVM provides high precision, and Neural Networks capture nonlinear patterns. However, each model individually has certain limitations. By combining these models using ensemble techniques, the hybrid approach reduces errors and improves overall performance. The results clearly demonstrate that the hybrid model outperforms individual models in detecting botnet attacks. This confirms that integrating multiple algorithms enhances reliability and robustness in cybersecurity applications, making it suitable for IoT environments where attack patterns are complex and dynamic.




**Figure 2: Precision-Recall Analysis**

This figure shows the precision and recall values of the proposed model. Precision indicates how many detected attacks are actually correct, while recall measures how many actual attacks are successfully identified. The graph demonstrates that the hybrid model maintains high precision and recall, indicating fewer false positives and false negatives. This is crucial in IoT security systems, where missing an attack or generating false alerts can cause serious issues. The balanced performance between precision and recall highlights the effectiveness of the hybrid model. The figure confirms that the system can accurately detect botnet attacks while minimizing unnecessary alerts, ensuring efficient and reliable intrusion detection.



**Figure 3: Detection Rate vs False Positive Rate**

This figure represents the relationship between detection rate and false positive rate. A high detection rate with a low false positive rate is ideal for any intrusion detection system. The graph shows that the hybrid model achieves a high detection rate while keeping false positives minimal. This indicates that the system is capable of identifying most attacks without misclassifying normal traffic. This balance is important in real-world applications, where excessive false alarms can reduce system trust. The figure demonstrates that the hybrid model provides a strong trade-off between detection efficiency and accuracy.



**Figure 4: Feature Importance Analysis**

This figure highlights the importance of different network traffic features in detecting botnet attacks. Features such as packet size, flow duration, and protocol type have a higher impact on prediction accuracy. The graph shows that certain features contribute more significantly to the model's decision-making process. Understanding feature importance helps in improving model performance by focusing on the most relevant attributes. It also reduces computational complexity by eliminating unnecessary features. This figure demonstrates that feature selection plays a critical role in enhancing the efficiency of the detection system.

## V.CONCLUSION

The proposed Hybrid Machine Learning Model for Efficient Botnet Attack Detection in IoT Environment provides a robust and scalable solution for enhancing IoT security. By combining multiple machine learning algorithms such as Random Forest, Support Vector Machine (SVM), and Neural Networks, the system effectively improves detection accuracy and reduces false positives. The hybrid approach leverages the strengths of each individual model, resulting in better performance compared to standalone techniques. The results clearly demonstrate that the system achieves high accuracy, improved detection rates, and efficient classification of network traffic into normal and malicious categories. The system also supports real-time monitoring and alert generation, enabling quick identification of botnet attacks and reducing potential damage. Feature importance analysis helps in identifying key network parameters that influence attack detection, thereby improving model efficiency. Additionally, the use of preprocessing techniques ensures that the model operates effectively even with large and complex datasets. Overall, this project highlights the importance of integrating multiple machine learning techniques to address complex cybersecurity challenges in IoT environments. The proposed system is efficient, adaptable, and suitable for real-world deployment. Future work can focus on incorporating deep learning models, real-time streaming data, and advanced threat intelligence to further enhance detection capabilities and system performance.

## REFERENCES

- [1] M. Antonakakis et al., "Understanding the Mirai botnet," in *Proc. USENIX Security Symposium*, 2017, pp. 1093–1110.
- [2] I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*. Cambridge, MA, USA: MIT Press, 2016.
- [3] S. Haykin, *Neural Networks and Learning Machines*, 3rd ed. New York, NY, USA: Pearson, 2009.
- [4] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems," in *Proc. Military Communications and Information Systems Conf.*, 2015, pp. 1–6, doi: 10.1109/MilCIS.2015.7348942.
- [5] I. Sharafaldin, A. Lashkari, and A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *Proc. ICISSP*, 2018, pp. 108–116, doi: 10.5220/0006639801080116.
- [6] S. Raza, L. Wallgren, and T. Voigt, "SVELTE: Real-time intrusion detection in IoT," *Ad Hoc Networks*, vol. 11, no. 8, pp. 2661–2674, Nov. 2013, doi: 10.1016/j.adhoc.2013.04.014.
- [7] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, Oct. 2001, doi: 10.1023/A:1010933404324.
- [8] C. Cortes and V. Vapnik, "Support-vector networks," *Machine Learning*, vol. 20, no. 3, pp. 273–297, Sep. 1995, doi: 10.1007/BF00994018.
- [9] A. Krizhevsky, I. Sutskever, and G. Hinton, "ImageNet classification with deep convolutional neural networks," in *Advances in Neural Information Processing Systems*, vol. 25, 2012.
- [10] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE CVPR*, 2016, pp. 770–778, doi: 10.1109/CVPR.2016.90.
- [11] J. Redmon et al., "You Only Look Once: Unified, real-time object detection," in *Proc. IEEE CVPR*, 2016, pp. 779–788, doi: 10.1109/CVPR.2016.91.
- [12] R. Girshick, "Fast R-CNN," in *Proc. IEEE ICCV*, 2015, pp. 1440–1448, doi: 10.1109/ICCV.2015.169.

- [13] O. Russakovsky et al., "ImageNet large scale visual recognition challenge," *Int. J. Comput. Vis.*, vol. 115, no. 3, pp. 211–252, Dec. 2015, doi: 10.1007/s11263-015-0816-y.
- [14] J. Long, E. Shelhamer, and T. Darrell, "Fully convolutional networks for semantic segmentation," in *Proc. IEEE CVPR*, 2015, pp. 3431–3440, doi: 10.1109/CVPR.2015.7298965.
- [15] A. Graves, *Supervised Sequence Labeling with Recurrent Neural Networks*. Berlin, Germany: Springer, 2012.
- [16] D. Silver et al., "Mastering the game of Go with deep neural networks and tree search," *Nature*, vol. 529, no. 7587, pp. 484–489, Jan. 2016, doi: 10.1038/nature16961.
- [17] A. G. Howard et al., "MobileNets: Efficient convolutional neural networks for mobile vision applications," *arXiv preprint arXiv:1704.04861*, 2017.
- [18] M. Tan and Q. V. Le, "EfficientNet: Rethinking model scaling," in *Proc. ICML*, 2019, pp. 6105–6114.
- [19] A. Dosovitskiy et al., "An image is worth 16×16 words: Vision transformers," in *Proc. ICLR*, 2021.
- [20] P. Viola and M. Jones, "Rapid object detection using a boosted cascade," in *Proc. IEEE CVPR*, 2001, pp. 511–518, doi: 10.1109/CVPR.2001.990517.
- [21] D. G. Lowe, "Distinctive image features from scale-invariant keypoints," *Int. J. Comput. Vis.*, vol. 60, no. 2, pp. 91–110, Nov. 2004, doi: 10.1023/B:VISI.0000029664.99615.94.
- [22] R. Szeliski, *Computer Vision: Algorithms and Applications*. London, U.K.: Springer, 2010.
- [23] H. C. Shin et al., "Deep CNN for computer-aided detection," *IEEE Trans. Med. Imaging*, vol. 35, no. 5, pp. 1285–1298, May 2016, doi: 10.1109/TMI.2016.2528162.
- [24] F. Chollet, *Deep Learning with Python*. Shelter Island, NY, USA: Manning, 2017.
- [25] J. Brownlee, *Machine Learning Mastery with Python*. 2016.
- [26] A. Javaid, Q. Niyaz, W. Sun, and M. Alam, "A deep learning approach for network intrusion detection system," in *Proc. 9th EAI Int. Conf. Bio-Inspired Information and Communications Technologies*, 2016, pp. 21–26, doi: 10.4108/eai.3-12-2015.2262516.
- [27] Q. Niyaz, W. Sun, and A. Javaid, "A deep learning based DDoS detection system in software-defined networking (SDN)," *EAI Endorsed Trans. Security and Safety*, vol. 4, no. 12, pp. 1–10, 2016, doi: 10.4108/eai.28-12-2016.2266469.
- [28] M. Roesch, "Snort: Lightweight intrusion detection for networks," in *Proc. 13th USENIX Conf. System Administration*, 1999, pp. 229–238.
- [29] G. D. Creech and J. Hu, "A semantic approach to host-based intrusion detection systems," *IEEE Trans. Dependable Secure Comput.*, vol. 11, no. 6, pp. 491–503, Nov.–Dec. 2014, doi: 10.1109/TDSC.2014.2317297.
- [30] A. Patcha and J. M. Park, "An overview of anomaly detection techniques: Existing solutions and latest technological trends," *Computer Networks*, vol. 51, no. 12, pp. 3448–3470, Aug. 2007, doi: 10.1016/j.comnet.2007.02.001.
- [31] Y. Meidan et al., "Detection of unauthorized IoT devices using machine learning techniques," *arXiv preprint arXiv:1709.04647*, 2017.

- [32] H. Sedjelmaci, S. M. Senouci, and N. Ansari, "Intrusion detection and ejection framework against lethal attacks in IoT," *IEEE Internet of Things Journal*, vol. 4, no. 6, pp. 2163–2174, Dec. 2017, doi: 10.1109/JIOT.2017.2705043.
- [33] M. Alrawashdeh and C. Purdy, "Toward an online anomaly intrusion detection system based on deep learning," in *Proc. IEEE Int. Conf. Machine Learning and Applications*, 2016, pp. 195–200, doi: 10.1109/ICMLA.2016.0039.
- [34] S. Zhao, W. Li, and Y. Zeng, "Intrusion detection system based on feature selection and ensemble learning," *IEEE Access*, vol. 7, pp. 108247–108256, 2019, doi: 10.1109/ACCESS.2019.2933142.
- [35] M. Abeshu and N. Chilamkurti, "Deep learning: The frontier for distributed attack detection in fog-to-things computing," *IEEE Communications Magazine*, vol. 56, no. 2, pp. 169–175, Feb. 2018, doi: 10.1109/MCOM.2018.1700332.